

Warning

For dimming with connected APP/Hub only. It is not recommended to use the SMART LIGHT bulbs with a line voltage dimmer. Each connected bulb contains a wireless radio and by reducing, or removing power through a line voltage dimmer may cause damage to the connected bulb electronics.




Smart Light



Get started

1. Insert the light bulb into the lamp socket.

2. Open the Heimgard app and follow the steps listed here to connect to your device



3. Toggle power from OFF to ON, on your lamp, the bulb will flash 2 times quickly when it starting the join process to connect to your hub.

Important safety information

1. Read through these instructions and follow accordingly.
2. Switch off the power supply to the lamp socket and allow sufficient time for the bulb to cool before removing the bulb from the socket.
3. Not suitable with standard wall dimmers
4. Clean only with dry soft cloth. Household cleaners and solvents can damage the finish on your device.
5. Do not install near any heat sources such as radiators, heat registers, stoves or other device that produce heat.
6. Do not use this device near water.
7. Warning: To reduce the risk of fire or electric shock, do not expose this device to rain or moisture.
8. Do not expose device to dripping or splashing.
9. All servicing should be performed by qualified service personnel. Servicing is required when the device has been damaged in any way.
10. Operating temperature: -20°C to +40°C



Dispose the product properly at the end of life. This is electronic waste which should be recycled accordingly.

4. The light bulb will flash once when it has been successfully "included" into your Zigbee network.
5. Your device will appear in the Found Devices list. Click configure to add the device to a specific room.

Need help?

Website: heimgard.com/support
Email: support@heimgard.com
Facebook: facebook.com/heimgardnorge/
Telephone: +47 649 44 422

Visit heimgard.com for more information.

Factory reset

Toggle the bulb ON and OFF 6 times for intervals of 0.5-2 seconds. Make sure there are no other switching actions below 3 seconds before the first switch. The sixth time you turn on the bulb, wait for 2 seconds, the bulb will flash twice indicating that it's successfully reset.

